


### ■ Features :

- MOVPE Epi Wafer
- Suitable for New Creative Products

### ■ Typical Applications :

- Automotive Signal Lamps: Stop/ Tail Lights
- Automotive Interior Lighting
- Commercials

### ■ Outline Dimensions : (Unit: $\mu\text{m}$ )



### ■ Physical Structure :

Chip dimension	Chip size	210 $\mu\text{m}$ x 210 $\mu\text{m}$
	Thickness	180 $\mu\text{m}$
	Emission area	195 $\mu\text{m}$
	Bonding pad	100 $\mu\text{m}$
Electrode	Top: P (anode)	Aluminum (Gold optional)
	Backside: N (cathode)	Gold alloy
Surface condition	Not frosted	

### ■ Electro-Optical Characteristics : ( $T_a = 25^\circ\text{C}$ )

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Forward Voltage	$V_F$	$I_F = 20 \text{ mA}$	-	2.00	2.40	V
Reverse Voltage	$V_R$	$I_R = 10 \text{ uA}$	5	-	-	V
Wavelength	$\lambda_p$	$I_F = 20 \text{ mA}$	-	644	-	nm
	$\lambda_D$		625	630	635	
Spectral width at half height	$\Delta \lambda$	$I_F = 20 \text{ mA}$	-	20	-	nm
Luminous Intensity	$I_v$	$I_F = 20 \text{ mA}$	80	-	-	mcd
			100	-	-	

■ Typical Electro-Optical Characteristics Curve:

Fig 1. Forward Current vs. Forward Voltage




Fig 2. Relative Intensity vs. Forward Current




Fig 3. Forward Voltage vs. Temperature




Fig 4. Relative Intensity vs. Temperature




Fig 5. Relative Intensity vs. Wavelength

